



FIND YOUR NEAREST DEALER

[PRODUCTS](#)
[SERVICE & SUPPORT](#)
[PARTS](#)
[ABOUT](#)

Site search

Home > Products > Reduced-Tail-Swing Excavators > ZX135US-6

# ZX135US-6

## Ultrashort Excavator

<b>Net Power</b>	75 kW (101 hp)
<b>Operating Weight</b>	14 300 kg (31,500 lb.)
<b>Max Dig Reach</b>	8.86 m (29 ft. 1 in.)
<b>Max Dig Depth</b>	5.98 m (19 ft. 7 in.)

LOCATE DEALER

COMPARE TO COMPETITORS



### Perfectly packaged production

With a tight tail-swing radius, the ZX135US-6 is perfect for contractors working in and around obstacles. The Dash-6 model is equipped with a powerful EPA Final Tier 4 (FT4)/EU Stage IV Isuzu engine that features integrated, effective engine technologies and does not require a diesel particulate filter. It also includes many other customer-driven features such as a standard rearview camera, standard factory installed auxiliary hydraulics with programmable attachment modes, and upperstructure handrails.

The ZX135US-6 comes standard equipped with five years of ZLink™ Ultimate, giving you 24/7 online access to machine location, health, utilization, fuel consumption, and other valuable information – so you can better understand costs and jobsite performance.

#### Downloads

[Features and Specs Brochure](#)

## FEATURES

+ Expand All Features

Engine	+
Durable structure and undercarriage	+
Hydraulics	+
Simple controls	+
Comfortable cab	+
Easy to maintain	+
ZLink™	+

## SPECIFICATIONS

– Expand All Specifications

Driveline	–
Emission Rating	Tier 4
Number Of Cylinders (Per Engine)	4
Displacement	3 ltr 182 Inches³
Rated speed	2000 rpm
Engine Output - Net	75 kW 101 hp
Number Of Carrier Rollers - Each	1

## Side

Number Of Track Rollers - Each Side 7

Track Shoe Width 700 mm  
28 inches

## Dimensions

Transport Length Mono Boom 7390 mm  
24 ft 3 in ft/in

Transport Height - Maximum 2870 mm  
9 ft 5 in ft/in

Overall Undercarriage Width 2690 mm  
8 ft 10 in ft/in

Track Length On Ground 2880 mm  
9 ft 5 in ft/in

Undercarriage Overall Length 3580 mm  
11 ft 9 in ft/in

Tailswing Radius 1490 mm  
4 ft 11 in ft/in

Ground Clearance 410 mm  
16 inches

Width over standard tracks 2690 mm  
8 ft 10 in ft/in

Track Gauge 1990 mm  
6 ft 6 in ft/in

Digging Reach - Mono Boom 8860 mm  
29 ft 1 in ft/in

Ground Level Reach - Mono Boom 8720 mm  
28 ft 7 in ft/in

Dig Height - Mono Boom 9690 mm  
31 ft 9 in ft/in

Dump Height - Mono Boom 7220 mm  
23 ft 8 in ft/in

Dig depth - 2.44m / 8'ft flat bottom 5790 mm  
19 ft ft/in

Dig Depth - Mono Boom 5980 mm  
19 ft 7 in ft/in

## Capacities

Fuel Tank 220 ltr  
58 gallons (US)

Hydraulic Tank 60 ltr  
15.9 gallons (US)


## Performance

Ground Bearing Pressure 32 kPa  
4.64 PSI

Dipper Tearout 61 kN  
13710 lbf

## Weights

Operating Weight 14300 kg  
31500 lbs

 Download & Print

## COMPARE

Select models to compare to the Hitachi ZX135US-6

(Maximum of 3)

Closest comparison by

COMPARE MODELS

## HITACHI MODELS

HITACHI ZX 135 US-6

## COMPETITOR MODELS

- CATERPILLAR 312 E
- CATERPILLAR 314 D LCR
- DOOSAN DX 140 LC-3
- JCB JS 145 LC
- KOBELCO SK 140 SR LC-5
- KOMATSU PC 138 USLC-8
- LINK-BELT 135 MSR SPIN ACE
- LINK-BELT 145 X3 LC SPIN ACE
- LINK-BELT 145 X3 SPIN ACE LC
- LIUGONG CLG 915 D III
- TAKEUCHI TB 1140
- VOLVO EC 140 E

## GALLERY



Customize your solution.

BUILD YOUR OWN

[▶ Products](#) [▶ Service & Support](#) [▶ Parts](#) [▶ About](#)



Credit Information: [United States](#) | [Canada](#)

© 2015-2019 Deere & Company and Hitachi Construction Machinery Co, Ltd. All rights reserved. [Privacy and Data](#) | [Cookie Preferences](#)