



# ZX210-5 & ZX210LC-5

## Utility Excavator

<b>Net Power</b>	125 kW 168 hp
<b>Operating Weight</b>	20 115 - 20 715 kg 44,346 - 45,669 lb.
<b>Max Dig Reach</b>	9.92 m 32 ft. 7 in.
<b>Max Dig Depth</b>	6.68 m 21 ft. 11 in.

[LOCATE DEALER](#)[COMPARE TO COMPETITORS](#)

## Well-armed with power

The ZX210LC-5 and ZX210-5 are forces to be reckoned with. These models are easy to transport and are designed for sewer and water contractors, basement diggers and for work in urban areas. An Isuzu engine delivers fuel-efficient and reliable performance; grouped service points simplify maintenance; a spacious cab keeps operators comfortable and more.

Both machines come standard equipped with five years of ZXLink™ Ultimate, giving you 24/7 online access to machine location, health, utilization, fuel consumption, and other valuable information – so you can better understand costs and jobsite performance.

## FEATURES

[+ Expand All Features](#)

Engine	+
Durable structure and undercarriage	+
Hydraulics	+
Simple controls	+
Comfortable cab	+
Easy to maintain	+
ZXLink™	+

## SPECIFICATIONS

[— Expand All Specifications](#)

Driveline	—
Emission Rating	Tier 2
Number Of Cylinders (Per Engine)	6
Displacement	6.5 ltr 396 Inches³
Rated speed	2100 rpm
Engine Output - Net	125 kW 168 hp

Number Of Carrier Rollers - Each Side	2
Number Of Track Rollers - Each Side	7
Track Shoe Width	700 mm 28 inches

Dimensions

Transport Length Mono Boom	9530 mm 31 ft 3 in ft/in
Transport Height - Maximum	3180 mm 10 ft 5 in ft/in
Overall Undercarriage Width	2920 mm 9 ft 7 in ft/in
Track Length On Ground	3350 mm 11 ft ft/in
Undercarriage Overall Length	4170 mm 13 ft 8 in ft/in
Tailswing Radius	2890 mm 9 ft 6 in ft/in
Ground Clearance	450 mm 18 inches
Width over standard tracks	2920 mm 9 ft 7 in ft/in
Track Gauge	2220 mm 7 ft 3 in ft/in
Digging Reach - Mono Boom	9920 mm 32 ft 7 in ft/in
Ground Level Reach - Mono Boom	9750 mm 32 ft ft/in
Dig Height - Mono Boom	10040 mm 32 ft 11 in ft/in
Dump Height - Mono Boom	7180 mm 23 ft 7 in ft/in
Dig depth - 2.44m / 8'ft flat bottom	6500 mm 21 ft 4 in ft/in
Dig Depth - Mono Boom	6680 mm 21 ft 11 in ft/in

Capacities


Fuel Tank	403 ltr 106.5 gallons (US)
Hydraulic Tank	135 ltr 35.7 gallons (US)

Performance

Ground Bearing Pressure	39 kPa 5.66 PSI
Dipper Tearout	114 kN 25629 lbf

Weights

Operating Weight	20115 kg 44346 lbs
------------------	-----------------------

 Download & Print

# COMPARE

Select models to compare to the Hitachi ZX210-5 & ZX210LC-5  
(Maximum of 3)

Closest comparison by 

Operating Weight



## HITACHI MODELS

☒ HITACHI ZX 210-5

## COMPETITOR MODELS

- ☐ CATERPILLAR 320 B L
- ☐ CATERPILLAR 320 C ME
- ☐ CATERPILLAR 320 D 2 GC
- ☐ CATERPILLAR EL 200 B
- ☐ JCB JS 190 LC
- ☐ JCB JS 190 LC
- ☐ JOHN DEERE 180G LC
- ☐ LIEBHERR R 900 C LITRONIC NLC
- ☐ LIEBHERR R 918 LITRONIC LC
- ☐ LINK-BELT 210 LX
- ☐ VOLVO EC 200 E L
- ☐ VOLVO EC 200 E NL

## GALLERY



Customize your solution.

BUILD YOUR OWN

[► Products](#)
[► Service & Support](#)
[► Parts](#)
[► About](#)



Credit Information: [United States](#) | [Canada](#)

© 2015-2019 Deere & Company and Hitachi Construction Machinery Co, Ltd. All rights reserved. [Privacy and Data](#) | [Cookie Preferences](#)