

BPU4045A »
 Reversible Vibratory Plates

Information

[Description](#)
[Technical specifications](#)
[Info material](#)
[Model variations](#)
[Product comparison](#)
[Product Inquiry](#)
[Dealer Locator](#)

**CALIFORNIA
 PROPOSITION 65
 WARNING**

BPU4045A Technical specifications

[Metric »](#)
[Imperial »](#)

BPU 4045A

Operating data

Operating weight	710 lb
Centrifugal force	8,992 lbf
Base plate size (W x L)	17.7 x 35.4 in
Base plate thickness	0.5 in
Height (without guide handle)	28.5 in
Operating width (without extension plate)	17.7 in
Operating width (with extension plate)	24 in
Frequency	69 Hz
Advance travel max. (depending on soil and environmental factors)	78.7 ft/min
Surface capacity max. (depending on soil and environmental factors)	9,300 ft ² /h

Engine / Motor

Engine / Motor type	Air-cooled single-cylinder, four-cycle gasoline engine
Engine / Motor manufacturer	Honda
Engine / Motor	GX 270
Displacement	16.5 in ³
at rpm	3,600 rpm
Operating performance max. (DIN ISO 3046)	8 hp
Operating performance (DIN ISO 3046)	6.2 hp
at rpm	2,600 rpm
Fuel consumption	0.42 US gal/h
Tank capacity (fuel)	5.6 US qt
Power transmission	From drive motor via centrifugal clutch and V-belt direct to exciter.

These products might also interest you:

