

**SW28** »  
Skid Steer Loaders

- Information
- Description
- Technical specifications**
- Dimensions
- Info material
- Attachments
- Standard components
- Options
- Model variations
- Product comparison
- Product inquiry

Dealer Locator

**CALIFORNIA PROPOSITION 65 WARNING**

## SW28 Technical specifications

[Metric](#) » [Imperial](#) »

| Operating data                                     |  |
|--|--|
| Height top of ROPS                                 | 81.9 in                                |
| Overall length w/ bucket                           | 143.9 in                               |
| Overall length w/o bucket                          | 115.8 in                               |
| Operating weight                                   | 8,253 lb                               |
| Height Hinge Pin Max                               | 134.6 in                               |
| Rated Operating Capacity 50%                       | 2,800 lb                               |
| Dump height max. at max height                     | 107.1 in                               |
| Angle of departure                                 | 25 °                                   |
| Tipping angle (bucket dump) w/bucket at max height | 38 °                                   |
| Tipping angle (bucket dump) w/bucket pin @ 124 in  | 45.5 °                                 |
| Ground clearance                                   | 9.4 in                                 |
| Breakout force max. - Bucket                       | 6,717 lbf                              |
| Breakout force max. - Boom                         | 5,705 lbf                              |
| Bucket width                                       | 72 in                                  |
| Width w/o bucket                                   | 70 in                                  |
| Wheelbase  | 45.8 in                                |
| Engine / Motor                                     |  |
| Engine / Motor                                     | Turbo-Charged Perkins 854 Tier 4 Final |
| Engine performance                                 | 74 hp                                  |
| Tank capacity                                      | 24.3 US gal                            |
| Hydraulic system                                   |  |
| Auxiliary Hydraulics- Standard Flow                | 22.5 US gpm                            |
| Auxiliary Hydraulics- High Flow                    | 35.9 US gpm                            |
| Pressure aux. relief                               | 3,338 psi                              |
| Power transmission                                 |  |
| Travel speed (low)                                 | 6.8 mph                                |
| Travel speed (high)                                | 11.2 mph                               |

These products might also interest you:

