

EZ28 »
Tracked Zero Tail Excavators

- Information
- Description
- Technical specifications**
- Dimensions
- Info material
- Attachments
- Standard components
- Options
- Model variations
- Product comparison
- Product Inquiry

Dealer Locator 

CALIFORNIA PROPOSITION 65 WARNING

EZ28 Technical specifications

Metric » Imperial »

Operating data	
Shipping weight min.	5,677 lb
Operating weight	6,030 - 7,456 lb
Biting force max.	3,440 lbf
Breakout force max. max.	5,058 lbf
Digging depth max.	108 in
Dumping height	111.8 - 121.5 in
Digging radius max.	189.21 in
L x W x H	167.5 x 61.8 x 94.8 in
Engine / Motor	
Engine / Motor manufacturer	Yanmar
Engine / Motor type	3TNV80F
Engine / Motor	Water-cooled 3-cylinder diesel engine
Displacement	77.2 in³
RPM / speed	2,500 rpm
Engine performance output to ISO	21.2 hp
Battery	44 CCA
Fuel tank capacity	9.3 US gal
Hydraulic system	
Duty pump	Double variable- & two-gear pump
Flow rate	23.6 US gpm
Operating pressure for working and traction hydraulics	3,263 psi
Operating pressure Slewing gear	2,988 psi
Hydraulic oil tank	7 US gal
Undercarriage	
Travel speed max.	2.4 mph
Chain width	11.8 in
Ground clearance	10.9 in
Dozer Blade	
Width	61.8 in
Height	11.4 in
Stroke - Above ground	15 in
Stroke - Below ground	16.5 in
Sound level	
Sound level (LwA) acc. to 2000/14/EC	93 dB(A)
Cabin - specified sound pressure level LpA acc. to ISO 6394	79 dB(A)

These products might also interest you:

