

**EZ53 »**

Tracked Zero Tail Excavators

Information

Description

**Technical specifications**

Dimensions

Info material

Attachments

Standard components

Options

Model variations

Product comparison

Product Inquiry

Dealer Locator

**CALIFORNIA  
PROPOSITION 65  
WARNING**

**EZ53 Technical specifications**

Metric »

Imperial »

**Operating data**

Shipping weight min.	10,937 lb
Operating weight	11,539 - 14,178 lb
Biting force max.	6,295 lbf
Breakout force max.	8,565 lbf
Digging depth max.	147.7 in
Dumping height	144.8 - 155.2 in
Digging radius max.	245.4 in
Superstructure slewing speed	9.2 rev/min
L x W x H	216.5 x 78.3 x 101.3 in

**Engine / Motor**

Engine / Motor manufacturer	Perkins
Engine / Motor type	404F-22T
Engine / Motor	Water-cooled 4-cylinder diesel engine EPA III
Displacement	135.2 in³
RPM / speed	2,440 rpm
Engine performance acc. to ISO	58.9 hp
Battery	88 CCA
Fuel tank capacity	21.9 US gal

**Hydraulic system**

Duty pump	Double variable- & two-gear pump
Flow rate	41.6 US gpm
Operating pressure for working and traction hydraulics	3,336 psi
Operating pressure Slewing gear	2,756 psi
Hydraulic oil tank	19.3 US gal

**Undercarriage**

Travel speed max.	2.9 mph
Chain width	15.7 in
Ground clearance	12.7 in

**Dozer Blade**

Width	78.3 in
Height	15 in
Stroke - Above ground	16.3 in
Stroke - Below ground	17.9 in

**Sound level**

Sound level (LwA) acc. to 2000/14/EC	94 dB(A)
Cabin - specified sound pressure level LpA acc. to ISO 6394	78 dB(A)

These products might also interest you:

